

Electrostivuitoare Netlift 3.5t-4t-4.5t-5t

1	Model		ND135T-MWS3	ND160T-MXWS3	ND140T-MWK3	ND160T-MWK3	ND180T-MWK3	ND200T-MWM3	ND230T-MWM3	ND250T-MWM3	ND280T-MWT3	ND300T-MWT3	ND320T-MWT3
2	Power type		Dizel	Dizel	Dizel	Dizel	Dizel	Dizel	Dizel	Dizel	Dizel	Dizel	Dizel
3	Rated capacity	kg	13500	16000	14000	16000	18000	20000	23000	25000	28000	30000	32000
4	Load centre	mm	900	600	1220	1220	1220	1220	1220	1220	1220	1220	1220
5	Lift height	mm	4000	4000	4000	4000	4000	4000	4000	4000	4000	4000	4000
6	Mast tilt angle	F/R	*	6° / 12°	6° / 12°	6° / 12°	6° / 12°	6° / 12°	6° / 12°	6° / 12°	6° / 12°	6° / 12°	6° / 12°
7	L x W x T	mm	1800 x 200 x 90	1500 x 200 x 90	2440x250x100	2440x250x110	2440x300x105	2440x300x110	2440x300x110	2440x300x110	2440x300x116	2440x320x110	2440x320x110
8	Fork	Regulating range	mm	840 - 2200	720 - 2200	910 - 2240	910 - 2240	910 - 2240	1040 - 2660	1040 - 2660	1040 - 2660	1500 - 3120	1500 - 3120
9		Max. side shifter	mm	630 (±315)	630 (±315)	660 (±325)	660 (±330)	660 (±330)	810 (±405)	810 (±405)	810 (±405)	810 (±405)	810 (±405)
10	Min.ground clearance (Bottom of mast)	mm	250	250	220	220	220	300	300	300	300	300	300
11	Overall length	mm	7150	6890	8300	8300	8300	9240	9240	9240	9740	9740	9740
12	Overall width	mm	2430	2430	2535	2535	2535	3020	3020	3020	3420	3420	3420
13	Overall height / driver cab	mm	3190	3190	3280	3280	3280	3580	3580	3580	3800	3800	3800
14	Overall height / mast	mm	3870	3870	3920	3920	3920	4250	4250	4250	4300	4300	4300
15	Turning radius (outside)	mm	4700	4700	5300	5300	5300	6270	6270	6270	6550	6550	6550
16	Tyre	Front	mm	11.00 - 20 - 18PR	12.00 - 20 - 20PR	1200 - 24 - 20PR	1200 - 24 - 20PR	1200 - 24 - 20PR	1400 - 24 - 24PR	1400 - 24 - 28PR	1400 - 24 - 28PR	1600 - 25 - 32PR	1600 - 25 - 32PR
17		Rear	mm	11.00 - 20 - 18PR	12.00 - 20 - 20PR	1200 - 20 - 20PR	1200 - 20 - 20PR	1200 - 20 - 20PR	1400 - 24 - 24PR	1400 - 24 - 28PR	1400 - 24 - 28PR	1600 - 25 - 32PR	1600 - 25 - 32PR
18	Tread	Front	mm	1743	1743	1850	1850	1850	2200	2200	2200	2490	2490
19		Rear	mm	2050	2050	2120	2120	2120	2300	2300	2300	2470	2470
20	Wheelbase	mm	3500	3500	3800	3800	3800	4500	4500	4500	4800	4800	4800
21	Travel (Unladen)	km/h	26	26	30	30	30	28	28	28	26	26	26
22	Speed	Lifting (Laden)	mm/sec	350	330	320	320	320	300	300	300	270	270
23		Lowering (Laden)	mm/sec	380	380	380	380	380	330	330	330	310	310
24	Max. Drawbar pull (Laden)	KN	100	120	125	125	125	160	160	160	250	250	250
25	Max. Gradeability	%	22	22	25	25	25	25	25	25	20	20	20
26	Self weight	kg	21000	22000	25600	25800	26300	35200	35400	36400	41000	42500	44000
27	Battery / Voltage-capacity	V / Ah	24/180	24/180	2 x 12 / 120	2 x 12 / 120	2 x 12 / 120	2 x 12 / 120	2 x 12 / 120	2 x 12 / 120	2 x 12 / 120	2 x 12 / 120	2 x 12 / 120
28	Transmission Type		3WG171	3WG171	3WG171	3WG171	3WG171	3WG211	3WG211	3WG211	3WG211	3WG211	3WG211
29	Transmission Stage		3 / 3	3 / 3	3 / 3	3 / 3	3 / 3	3 / 3	3 / 3	3 / 3	3 / 3	3 / 3	3 / 3
30	Operating pressure (For attachments)	Mpa	19	19	19	19	19	21	21	21	21	21	21

ND135-160T WIDE VIEW MAST

Mast name	Max. Fork height (mm)	Overall height (mm)	Door frame weight of pallet fork (kg)		Load centre (mm)		Tilt angle (F/R)	
			ND135T	ND160T	ND135T	ND160T		
M300	3000	3370	5324	5350	900	600	6 ° / 12 °	13500
M350	3500	3620	5450	5480	900	600	6 ° / 12 °	13500
M400	4000	3870	5580	5615	900	600	6 ° / 12 °	13500
M450	4500	4120	5770	5790	900	600	6 ° / 12 °	13500
M500	5000	4420	6150	6070	900	600	6 ° / 6 °	13500
M550	5500	4670	6225	6175	900	600	3 ° / 6 °	12500
M600	6000	4970	6375	6300	900	600	3 ° / 6 °	11500

ND140T-160T-180T WIDE VIEW MAST

Mast name	Max. Fork height (mm)	Overall height (mm)	Load centre (mm)			Tilt angle (F/R)	Load capacity (kg)	
			ND140T	ND160T	ND180T		ND140T	ND160T
M300	3000	3420	1220	1220	1220	6 ° / 12 °	14000	16000
M350	3500	3670	1220	1220	1220	6 ° / 12 °	14000	16000
M400	4000	3920	1220	1220	1220	6 ° / 12 °	14000	16000
M450	4500	4170	1220	1220	1220	6 ° / 12 °	14000	16000
M500	5000	4420	1220	1220	1220	6 ° / 6 °	13200	15000
M550	5500	4670	1220	1220	1220	3 ° / 6 °	12500	14200
M600	6000	4920	1220	1220	1220	3 ° / 6 °	12000	13500

ND200T-230T-250T WIDE VIEW MAST

Mast name	Max. Fork height (mm)	Overall height (mm)	Load centre (mm)			Tilt angle (F/R)	Load capacity (kg)	
			ND200T	ND230T	ND250T		ND200T	ND230T
M300	3000	3420	1220	1220	1220	6 ° / 12 °	20000	23000
M350	3500	3670	1220	1220	1220	6 ° / 12 °	20000	23000
M400	4000	3920	1220	1220	1220	6 ° / 12 °	20000	23000
M450	4500	4170	1220	1220	1220	6 ° / 12 °	20000	23000
M500	5000	4420	1220	1220	1220	6 ° / 6 °	19400	22200
M550	5500	4670	1220	1220	1220	3 ° / 6 °	18900	21500
M600	6000	4920	1220	1220	1220	3 ° / 6 °	18500	21000

ND280T-300T-320T WIDE VIEW MAST

Mast name	Max. Fork height (mm)	Overall height (mm)	Load centre (mm)			Tilt angle (F/R)	Load capacity (kg)	
			ND280T	ND300T	ND320T		ND280T	ND300T
M400	4000	4500	1220	1220	1220	6 ° / 12 °	28000	30000
M450	4500	4750	1220	1220	1220	6 ° / 12 °	28000	30000
M500	5000	5000	1220	1220	1220	3 ° / 6 °	27000	28500

ND135T- 160T mini WIDE VIEW MAST

Mast name	Max. Fork height (mm)	Overall height (mm)	Load centre (mm)		Tilt angle (F/R)	Load capacity (kg)		Self weight (kg)	
			ND135T	ND160T		ND135T	ND160T	ND135T	ND160T
M300	3000	3370	900	600	6 ° / 12 °	13500	16000	5324	5350
M350	3500	3620	900	600	6 ° / 12 °	13500	16000	5450	5480
M400	4000	3870	900	600	6 ° / 12 °	13500	16000	5580	5615
M450	4500	4120	900	600	6 ° / 12 °	13500	16000	5770	5790
M500	5000	4420	900	600	6 ° / 6 °	13000	15000	6150	6070
M550	5500	4670	900	600	3 ° / 6 °	12500	14000	6225	6175
M600	6000	4970	900	600	3 ° / 6 °	11500	13000	6375	6300

1	Model		ND135T-MWS3	ND160T-MXWS3	ND140T-MWK3	ND160T-MWK3	ND180T-MWK3	ND200T-MWM3	
2	Power type		Dizel	Dizel	Dizel	Dizel	Dizel	Dizel	
3	Rated capacity	kg	13500	16000	14000	16000	18000	20000	
4	Load centre	mm	900	600	1220	1220	1220	1220	
5	Lift height	mm	4000	4000	4000	4000	4000	4000	
6	Mast tilt angle	F/R	°	6° / 12°	6° / 12°	6° / 12°	6° / 12°	6° / 12°	
7		L x W x T	mm	1800 x 200 x 90	1500 x 200 x 90	2440x250x100	2440x250x105	2440x250x110	2440x300x105
8	Fork	Regulating range	mm	840 - 2200	720 - 2200	910 - 2240	910 - 2240	910 - 2240	1040 - 2660
9		Max. side shifter	mm	630 (±315)	630 (±315)	660 (±325)	660 (±330)	660 (±330)	810 (±405)
10	Min. ground clearance (Bottom of mast)		mm	250	250	220	220	220	300
11	Overall dimensions	Overall length	mm	7150	6890	8300	8300	8300	9240
12		Overall width	mm	2430	2430	2535	2535	2535	3020
13		Overall height / driver cab	mm	3190	3190	3280	3280	3280	3580
14		Overall height / mast	mm	3870	3870	3920	3920	3920	4250
15	Turning radius (outside)		mm	4700	4700	5300	5300	5300	6270
16	Tyre	Front	mm	11.00 - 20 - 18PR	12.00 - 20 - 20PR	1200 - 24 - 20PR	1200 - 24 - 20PR	1200 - 24 - 20PR	1400 - 24 - 24PR
17		Rear	mm	11.00 - 20 - 18PR	12.00 - 20 - 20PR	1200 - 20 - 20PR	1200 - 20 - 20PR	1200 - 20 - 20PR	1400 - 24 - 24PR
18	Tread	Front	mm	1743	1743	1850	1850	1850	2200
19		Rear	mm	2050	2050	2120	2120	2120	2300
20	Wheelbase		mm	3500	3500	3800	3800	3800	4500
21	Speed	Travel (Unladen)	km/h	26	26	30	30	30	28
22		Lifting (Laden)	mm/sec	350	330	320	320	320	300
23		Lowering (Laden)	mm/sec	380	380	380	380	380	330
24	Max. Drawbar pull (Laden)		KN	100	120	125	125	125	160
25	Max. Gradeability		%	22	22	25	25	25	25
26	Self weight		kg	21000	22000	25600	25800	26300	35200
27	Battery / Voltage-capacity	V / Ah		24/180	24/180	2 x 12 / 120	2 x 12 / 120	2 x 12 / 120	2 x 12 / 120
28	Transmission Type			3WG171	3WG171	3WG171	3WG171	3WG171	3WG211
29	Transmission Stage			3 / 3	3 / 3	3 / 3	3 / 3	3 / 3	3 / 3
30	Operating pressure (For attachments)		Mpa	19	19	19	19	19	21



SC Stivuitoare-Lize SRL

Telefon: 0040 744 136 717

Email: office@stivuitoare-lize.ro

Website: <http://stivuitoare-lize.ro/>

Comuna Corunca, Str. Principala, nr. 412-413, judet Mures, Romania