

SC Stivuitoare-Lize SRL

Telefon: 0040 744 136 717

Email: office@stivuitoare-lize.ro

Website: <http://stivuitoare-lize.ro/>

Comuna Corunca, Str. Principala, nr. 412-413, judet Mures, Romania

Pompa hidraulica stivuator Jungheinrich SN

50048227 (204)




204

– SPECIFICATIONS

Type of pump	gearpump
Number of elements	2
Type of flange	type A
Diameter of flange mounting holes D1 (mm)	14.3
Center distance of mounting holes flange C1 (mm)	146
Total length of pump L1 (mm)	284
Neck diameter D2 (mm)	101.6
Type of shaft	type D
Distance from flange to end L2 (mm)	41.2
Diameter of shaft D3 (mm)	21.7
Number of splines	13
Direction of rotation	clockwise
Position of suction port 1st element, only for pump type T POS-C01	side
Type of connections suction port 1st element, only for pump type T TY-C0a	type D
Thread type of connections suction 1st element	7/16 UNC

Center distance between mounting holes C-C01a (mm)	58.7
Center distance between mounting holes C-C02a (mm)	30.3
Position of pressure 1st element, only for pump type T POS-C02	side
Type of connections pressure 1st element, only for pump type T TY-C0b	type D
Thread type of connection pressure port 1st element TA-C0b	3/8 UNC
Center distance between mounting holes C-C01b (mm)	47.6
Center distance between mounting holes C-C02b (mm)	22.3
Flow control valve present	YES
Biggest Thread type valve TA3	1 1/16 UNF
Second Thread type valve TA4	3/4 UNF
Material of the housing	aluminium









Pompa h






— SPECIFICATIONS

Type of pump	gearpump
Number of elements	2
Type of flange	type A
Diameter of flange mounting holes D1 (mm)	14.3
Center distance of mounting holes flange C1 (mm)	146
Total length of pump L1 (mm)	284
Neck diameter D2 (mm)	101.6
Type of shaft	type D
Distance from flange to end L2 (mm)	41.2
Diameter of shaft D3 (mm)	21.7
Number of splines	13
Direction of rotation	clockwise
Position of suction port 1st element, only for pump type T P05-C01	side
Type of connections suction port 1st element, only for pump type T TY-C0a	type D
Thread type of connections suction 1st element	7/16 UNC

Center distance between mounting holes C-C01a (mm)	58.7
Center distance between mounting holes C-C02a (mm)	30.3
Position of pressure 1st element, only for pump type T P05-C02	side
Type of connections pressure 1st element, only for pump type T TY-C0b	type D
Thread type of connection pressure port 1st element TA-C0b	3/8 UNC
Center distance between mounting holes C-C01b (mm)	47.6
Center distance between mounting holes C-C02b (mm)	22.3
Flow control valve present	YES
Biggest Thread type valve TA3	1 1/16 UNF
Second Thread type valve TA4	3/4 UNF
Material of the housing	aluminium



SC Stivuitoare-Lize SRL

Telefon: 0040 744 136 717

Email: office@stivuitoare-lize.ro

Website: <http://stivuitoare-lize.ro/>

Comuna Corunca, Str. Principala, nr. 412-413, judet Mures, Romania