



SC Stivuitoare-Lize SRL

Telefon: 0040 744 136 717

Email: [office@stivuitoare-lize.ro](mailto:office@stivuitoare-lize.ro)

Website: <http://stivuitoare-lize.ro/>

Comuna Corunca, Str. Principala, nr. 412-413, judet Mures, Romania

# **Grup pompe hidraulice stivuator LINDE/0009810835 (1580)**

---



1580



**STILL**

Type **0009810835**

IP 43 Isol. **2,2kW** **24Vdc**

Bar code



13-04-07  
0009810835  
0009810835



Skra AMJ 5772  
11-216.479  
2,2kW 24V 120A 6,0Nm  
3000min<sup>-1</sup>  
2.0min  
S3=5%ED  
F CE  
IP54

1580

STILL  
9810835  
2,2kW 24Vdc

Type of pump group TY-PG	motor-pump-reservoir	Brief operation (min)	2
Length L1 (mm)	346	Intermittent operation (%)	5
Width B1 (mm)	181	Starter relay present	NO
Height H1 (mm)	175	Direction of rotation hydraulic pump	counterclockwise
Function	lifting	Length L2 (mm)	142
AC / DC	direct current	Diameter reservoir D5 (mm)	126
Minimum voltage U1 (V)	24	Position	vertical
Current I (A)	120	Decompression	electrical
Revolutions per minute (tr/min)	2600	Tension of the valve U4 (V)	24
Power (kW)	2.2	Type of cilinder TY-CI	single acting (one gate)
Cooling fan present	NO	Lowering choke proportional with pump	NO
Direction of rotation motor	clockwise	Greutate (kg)	10.18
Continuous operation	NO		

**Grup pompe hidraulice stivuito LINDE/0009810835 (1580) Pret: 560€ fara TVA Se emite factura**

Type of pump group TY-PG	motor-pump-reservoir	Brief operation (min)	2
Length L1 (mm)	346	Intermittent operation (%)	5
Width B1 (mm)	181	Starter relay present	NO
Height H1 (mm)	175	Direction of rotation hydraulic pump	counterclockwise
Function	lifting	Length L2 (mm)	142
AC / DC	direct current	Diameter reservoir D5 (mm)	126
Minimum voltage U1 (V)	24	Position	vertical
Current I (A)	120	Decompression	electrical
Revolutions per minute (tr/min)	2600	Tension of the valve U4 (V)	24
Power (kW)	2.2	Type of cilinder TY-CI	single acting (one gate)
Cooling fan present	NO	Lowering choke proportional with pump	NO
Direction of rotation motor	clockwise	Greutate (kg)	10.18
Continuous operation	NO		







**Iskra** AMJ 5772

11.216.479

2,2kW 24V 120A 6,0Nm

2600min<sup>-1</sup>



S2=2,0min S3=5%ED

IP 54

insulation  
class

F



Image not found or type unknown

SC Stivuitoare-Lize SRL

Telefon: 0040 744 136 717

Email: [office@stivuitoare-lize.ro](mailto:office@stivuitoare-lize.ro)

Website: <http://stivuitoare-lize.ro/>

Comuna Corunca, Str. Principala, nr. 412-413, judet Mures, Romania